



## Fully electric stacker 1.2 ton

REF 139TA7656



Belgian  
Quality

- Enables the operator to pick up loads accurately and cautiously
- Operator-friendly tiller head controls for improved load handling
- Complete with charger
- Complete with battery

Characteristics		
Drive unit		Battery
Operator type		Walkie
Load capacity	Q (kg)	1200
Load center	C (mm)	600
Load distance	X (mm)	700
Wheelbase	Y (mm)	1218
Weights		
Service weight (incl. battery)	Kg	1050
Axle loading, laden operator/load side	Kg	750 / 1500
Axle loading, unladen operator/load side	Kg	715 / 335
Wheels, Chassis		
Tyre type		Polyurethane
Tyre size, operator side (diameter x width)	mm	230 x 75
Tyre size, load side (diameter x width)	mm	85 x 70
Balance wheels (dimensions)	mm	85 x 50
Wheels, number operator/load side (x=drive wheels)		1x + ½
Tread, operator side	B10 (mm)	538
Tread, load side	B11 (mm)	380
Dimensions		
Height, mast lowered	H1 (mm)	1970
Free lift	H2 (mm)	100
Lift height	H3 (mm)	3600
Height, mast extended	H4 (mm)	3529
Height of tiller arm in operating position, min/max	H14 (mm)	825/1225
Fork height, lowered	H13 (mm)	85
Overall length	L1 (mm)	1826
Length to face of forks	L2 (mm)	676
Overall width	B1/b2 (mm)	800
Fork dimensions	Mm	1150
Outside fork width	B3 (mm)	550
Ground clearance	M2 (mm)	30
Aisle width, 1000x1200 pallet crossways	Ast (mm)	2370
Aisle width, 800 x 1200 pallet lengthways	Ast (mm)	2303
Outer turning radius	Wa (mm)	1463
Performance		
Travel speed, laden/unladen	Km/h	5/5.5
Lifting speed, laden/unladen	m/s	0.127 /0.15
Lowering speed, laden/unladen	m/s	0.23 / 0.22
Maximum gradeability, laden/unladen	%	8 / 16
Service brake		Electromagnetic
Drive		
Drive motor rating	kW	1.1
Lift motor rating	kW	2.2
Battery voltage/ rated capacity (5h)	V/Ah	24 / 210
Battery weight (with box)	Kg	205
Battery compartment dimensions l/w/h	Mm	650/540/200
Battery type		Industry battery
Others		
Type of drive control		AC
Manufacturer		ZAPI/CURTIS
Sound level at operator's ear	dB (A)	74

RATED CAPACITIES AND LOAD CENTRES GRAPH

