



EUROLIFTER STACKER

- Effortless lifting at an economical price.
- This lift is designed to handle skids, pallets, tools and dies, position work, feed machinery, and other handling tasks.
- The unit is operated by hydraulic foot pump together with handle, making lifting effortless, also foot pedal or handle lowering valve.
- Hydraulic cylinder with chrome-plated ram, also master fitted with heavy-duty roller bearings, with flow control valve located at base of lift cylinder that regulates lowering speed for safety.
- Steer with swivel casters for ease maneuverability, safety screen, foot operated swivel caster parking brake.
- Optional Quick lifting.
- Standard wheel brake.
- Roller chain with over 5 times capacity yield

SPECIFICATIONS ON THE BACK



EUROLIFTER STACKER

Reference			8159866	10513637	10513639	10513640
Lift Height	mm		1600	2500	1600	2500
Load Capacity	kg		1000		1500	
Load Center	mm		600		600	
Overall Fork Length & Width	mm		560x1150		560x1150	
Overall Height (A)	Fork lowered	mm	1770		2010	
	Raised height	mm	2010	2970	1770	2970
Overall Width	mm		700		700	
Overall Length	mm		1550		1550	
Fork Width	mm		160		160	
Wheel Size	Steering	mm	150		150	
	Front	mm	80		80	
Net Weight	kg		210	310	246	330

